





Our best-selling light truck tire, the Michelin® LTX® M/S tire helps provide exceptionally long-lasting, balanced performance in any condition, even mud and snow.



With MaxTouch Construction™



Without MaxTouch Construction™



Three Steel Belts

Get More Miles For Your Money*

The LTX M/S tire's MaxTouch Construction™ features a unique shape that helps deliver long-lasting, more uniform wear by evenly distributing the forces of acceleration, braking, and cornering.

Drive With Confidence In Nearly Any Weather

Full-depth sipes help deliver up to 15 percent better snow traction than the competition† and provide ultimate grip in almost any kind of weather.

Haul Heavier Loads

The only light truck tire to offer three steel belts in the D and E load ranges to handle loads up to 13,500 lbs.**

*Based on warranty rates of Michelin LTX series vs. other brands.

†Compared against Bridgestone® Dueler™ H/T, Goodyear Fortera® featuring TripleTred Technology,™ and Goodyear Wrangler® featuring SilentArmor Technology.™

**Using four LT265/75R16/E tires inflated at 80 psi.

Size	Service Desc.	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max. Load Single (lbs/psi)	Treadwear	Traction	Temperature	Original Equipment
P205/75R15	97S	ORWL	70051	5.0 - 7.0	8.1 on 5.5	27.0	13.0	777	1435@35*	500	A	B	
P215/75R15	100S	ORWL	23526	5.5 - 7.0	8.6 on 6.0	27.6	13.0	754	1584@35*	500	A	B	
P225/70R15	100S	ORWL	48079	6.0 - 7.5	9.0 on 6.5	27.4	13.0	765	1594@35*	500	A	B	MA
P225/75R15	102S	ORWL	76017	6.0 - 7.5	9.0 on 6.0	28.3	13.0	741	1703@35*	500	A	B	
P235/70R15	102S	ORWL	97679	6.0 - 8.0	9.4 on 7.0	27.9	13.0	746	1724@35*	500	A	B	
P235/75R15	105S	ORWL	26632	6.0 - 8.0	9.4 on 6.5	28.7	13.0	728	1844@35*	500	A	B	
P235/75R15/XL	108S	ORBL	57653	6.0 - 8.0	9.4 on 6.5	28.8	13.0	728	1985@41*	500	A	B	F
P235/75R15/XL	108S	ORWL	29394	6.0 - 8.0	9.4 on 6.5	28.8	13.0	728	1985@41*	500	A	B	F
P215/70R16	99S	ORWL	60041	5.5 - 7.0	8.7 on 6.5	27.8	13.0	755	1554@35*	500	A	B	
P225/70R16	101S	ORBL	62260	6.0 - 7.0	8.9 on 6.5	28.4	13.0	738	1654@35*	500	A	B	DC
P225/70R16	101S	ORWL	52470	6.0 - 7.0	8.9 on 6.5	28.4	13.0	738	1654@35*	500	A	B	
P235/70R16	104S	ORWL	59257	6.0 - 8.0	9.6 on 7.0	29.1	13.0	722	1804@35*	500	A	B	
P235/70R16/XL	107S	ORBL	66991	6.0 - 8.0	9.6 on 7.0	29.1	13.0	717	1954@41*	500	A	B	F
P235/70R16/XL	107S	ORWL	76721	6.0 - 8.0	9.6 on 7.0	29.1	13.0	717	1954@41*	500	A	B	F
P235/75R16	106S	ORWL	76374	6.0 - 8.0	9.4 on 6.5	29.9	13.0	696	1904@35*	500	A	B	
P245/70R16	106S	ORWL	84843	6.5 - 8.0	9.8 on 7.0	29.6	13.0	707	1904@35*	500	A	B	
P245/75R16	109S	ORWL	63571	6.5 - 8.0	9.7 on 7.0	30.4	13.0	684	2065@35*	500	A	B	
P255/65R16	106S	ORBL	61571	7.0 - 9.0	10.1 on 7.5	29.2	11.0	712	1904@35*	500	A	B	N, I
P255/70R16	109S	ORWL	39992	6.5 - 8.0	10.3 on 7.5	30.2	13.0	694	2065@35*	500	A	B	
P265/70R16	111S	ORWL	85423	7.0 - 8.5	10.7 on 8.0	30.7	13.0	681	2185@35*	500	A	B	
P265/75R16	114S	ORWL	97979	7.0 - 9.0	10.5 on 7.5	31.6	13.0	658	2365@35*	500	A	B	
P275/70R16	114H	ORBL	98835	7.0 - 10.0	11.1 on 8.0	31.3	12.0	666	2365@44*	440	A	A	T
P275/70R16	114S	ORBL	43428	7.0 - 10.0	11.1 on 8.0	31.3	12.0	666	2365@35*	500	A	B	L, T
P245/65R17	105S	ORBL	23007	7.0 - 8.5	9.6 on 7.0	29.7	11.0	700	1854@35*	440	A	B	HO
P255/70R17	110S	ORWL	02846	6.5 - 8.5	10.3 on 7.5	31.1	13.0	669	2125@44*	500	A	B	
P265/70R17	113S	ORWL	66259	7.0 - 8.5	10.8 on 8.0	31.8	13.0	656	2305@35*	500	A	B	
P275/55R20	111T	ORBL	59620	7.5 - 9.5	11.1 on 8.0	31.9	13.0	652	2185@44*	500	A	B	
P275/60R20	114T	ORBL	57848	7.5 - 9.5	11.0 on 8.0	33.0	13.0	630	2365@44*	500	A	B	
LT195/75R14/C	93/90R LRC	ORWL	10674	5.0 - 6.0	7.9 on 5.5	25.5	13.0	824	1435@50	1325@50			
LT215/75R15/C	100/97R LRC	ORWL	26820	5.5 - 7.0	8.7 on 6.0	27.7	13.0	755	1765@50	1610@50			
LT235/75R15/C	104/101R LRC	ORWL	78868	6.0 - 7.0	9.5 on 6.5	28.8	13.0	727	1985@50	1820@50			
30x9.50R15/C	104R LRC	ORWL	09418	6.5 - 8.5	9.6 on 7.0	29.6	15.0	706	1985@50				
31x10.50R15/C	109R LRC	ORWL	24798	7.0 - 9.0	11.1 on 9.0	30.8	15.0	679	2270@50				
32x11.50R15/C	113R LRC	ORWL	09478	8.0 - 10.0	11.6 on 9.0	31.7	15.0	662	2535@50				
LT215/85R16/D	110/107R LRD	ORBL	20898	5.0 - 7.0	8.7 on 6.0	30.5	15.0	685	2335@65	2150@65			
LT215/85R16/E	115/112R LRE	ORBL	57810	5.5 - 7.0	8.7 on 6.0	30.5	15.0	685	2680@80	2470@80			DC
LT225/75R16/D	110/107R LRD	ORBL	00978	6.0 - 7.0	9.1 on 6.0	29.3	15.0	709	2335@65	2150@65			
LT225/75R16/D	110/107R LRD	ORWL	20436	6.0 - 7.0	9.1 on 6.0	29.3	15.0	709	2335@65	2150@65			
LT225/75R16/E	115/112R LRE	ORBL	25516	6.0 - 7.0	8.8 on 6.0	29.4	15.0	709	2680@80	2470@80			F
LT225/75R16/E	115/112R LRE	ORWL	65141	6.0 - 7.0	8.8 on 6.0	29.4	15.0	709	2680@80	2470@80			F
LT235/85R16/D	114/111R LRD	ORBL	06854	6.0 - 7.0	9.2 on 6.5	31.9	15.0	655	2623@65	2381@65			
LT235/85R16/E	120/116R LRE	ORBL	07364	6.0 - 7.0	9.3 on 6.5	32.0	15.0	654	3042@80	2778@80			DC
LT235/85R16/E	120/116R LRE	ORWL	16658	6.0 - 7.0	9.3 on 6.5	32.0	15.0	654	3042@80	2778@80			
LT245/75R16/E	120/116R LRE	ORBL	22606	6.5 - 7.5	9.8 on 7.0	30.7	15.0	681	3042@80	2778@80			DC
LT245/75R16/E	120/116R LRE	ORWL	60856	6.5 - 7.5	9.8 on 7.0	30.7	15.0	681	3042@80	2778@80			DC
LT265/75R16/C	112/109R LRC	ORWL	10570	7.0 - 8.0	10.7 on 7.5	31.8	15.0	658	2470@50	2270@50			
LT265/75R16/E	123/120R LRE	ORWL	52169	7.0 - 8.0	10.7 on 7.5	31.8	14.0	652	3415@80	3085@80			F, DC
LT285/75R16/D	122/119R LRD	ORWL	78276	7.5 - 9.0	11.3 on 8.0	32.8	15.0	634	3305@65	3000@65			
LT235/80R17/E	120/117R LRE	ORWL	53346	6.0 - 7.5	9.3 on 6.5	31.8	15.0	654	3085@80	2835@80			

Original Equipment Key: DC = DaimlerChrysler, F = Ford, HO = Honda, I = Infiniti, L = Lexus, MA = Mazda, N = Nissan, T = Toyota
 XL = Extra Load

* Passenger sizes used in Light Truck/SUV applications have reduced load capacity. This will differ from the maximum load branded on the tire sidewall.
 Government UTQG Ratings do not apply to light truck-sized tires.

- The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
- Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owners manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires, and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owners manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.
 DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed. For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160 km/h (100 mph), load and inflation must be adjusted according to the table below.

S-Speed Rated Sizes:				T-Speed Rated Sizes:					H-Speed Rated Sizes:						
	Maximum Speed (mph)	100	106		112	118	Maximum Speed (mph)	100		106	112	118	124	130	
Inflation Increase (psi)	0	1	2		0	1	2	3		0	1	2	3	4	5
Load Capacity (% of max.)	100	100	100		100	100	100	100		100	100	100	100	100	100

