

# Michelin® Pilot® Exalto® A/S



Michelin® Pilot® Exalto® A/S tires combine a strong European sport handling flavor with the ingenuity of American all-season capability — all in a package that carries a 45,000-mile warranty.

### **Superb Wet Performance**

Deep, precisely cut HydroChutes™ help channel water away quickly, offering greater confidence in wet weather.

### **Even, Consistent Performance**

A Life Maximized Adherence™ all-season tread compound helps deliver extreme all-season grip that is able to maintain heightened performance season after season, year after year.

### **Exceptional Control And Confidence**

A European performance profile, featuring a rounder shoulder, is designed to provide progressive, predictable cornering, letting you fully enjoy all of your vehicles performance capabilities.

NOTE: These comparisons are among Michelin® Ultra-High Performance tires, unless specified otherwise.  
Copyright © 2007 Michelin North America, Inc. All rights reserved.  
MDL42922

Size	Service Desc.	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/2nds)	Revs/Mile at 45 mph	Max. Load Single (lbs@psi)	Treadwear	Traction	Temperature
185/60R14	82H	RRBL	99366	5.0 - 6.5	7.5 on 5.5	22.8	10.5	912	1047@44	400	A	A
195/60R14	86H	RRBL	10287	5.5 - 7.0	8.0 on 6.0	23.2	10.5	895	1168@44	400	A	A
195/50R15	82V	RRBL	01473	5.5 - 7.0	7.9 on 6.0	22.8	10.5	913	1047@44	400	A	A
195/55R15	85V	RRBL	07663	5.5 - 7.0	8.0 on 6.0	23.5	10.5	886	1135@44	400	A	A
195/60R15	88H	RRBL	07374	5.5 - 7.0	8.1 on 6.0	24.0	10.5	867	1235@44	400	A	A
195/65R15	91H	RRBL	16529	5.5 - 7.0	7.9 on 6.0	25.0	10.5	832	1356@44	400	A	A
205/55R15	88V	RRBL	84149	5.5 - 7.5	8.5 on 6.5	23.9	10.5	869	1235@44	400	A	A
205/60R15	91H	RRBL	27549	5.5 - 7.5	8.4 on 6.0	24.5	10.5	850	1356@44	400	A	A
205/65R15	94H	RRBL	18569	5.5 - 7.5	8.3 on 6.0	25.5	10.5	817	1477@44	400	A	A
215/65R15	96H	RRBL	24803	6.0 - 7.5	8.9 on 6.5	25.8	10.5	806	1565@44	400	A	A
225/60R15	96V	RRBL	35867	6.0 - 8.0	9.1 on 6.5	25.6	10.5	812	1565@44	400	A	A
195/50R16	84V	RRBL	12547	5.5 - 7.0	7.9 on 6.0	23.8	10.5	873	1102@44	400	A	A
205/60R16	87V	RRBL	37566	5.5 - 7.5	8.3 on 6.5	24.1	10.5	862	1201@44	400	A	A
205/55R16	91H	RRBL	29192	5.5 - 7.5	8.4 on 6.5	24.8	10.5	839	1356@44	400	A	A
205/55R16	91V	RRBL	30827	5.5 - 7.5	8.4 on 6.5	24.8	10.5	839	1356@44	400	A	A
215/55R16	93V	RRBL	36881	6.0 - 7.5	8.9 on 7.0	25.3	10.5	822	1433@44	400	A	A
215/60R16	95H	RRBL	29299	6.0 - 7.5	8.9 on 6.5	26.0	10.5	800	1521@44	400	A	A
215/60R16	95V	RRBL	83775	6.0 - 7.5	8.9 on 6.5	26.0	10.5	800	1521@44	400	A	A
225/50R16	92H	RRBL	16231	6.0 - 8.0	9.1 on 7.0	24.9	10.5	834	1389@44	400	A	A
225/50R16	92V	RRBL	23742	6.0 - 8.0	9.1 on 7.0	24.9	10.5	834	1389@44	400	A	A
225/55R16	95H	RRBL	36771	6.0 - 8.0	9.2 on 7.0	25.8	10.5	806	1521@44	400	A	A
205/50R17	89V	RRBL	18880	5.5 - 7.5	8.4 on 6.5	25.2	10.5	824	1279@44	400	A	A
215/50R17	91H	RRBL	22737	6.0 - 7.5	8.6 on 7.0	25.5	10.5	816	1356@44	400	A	A
225/45R17	91H	RRBL	34129	7.0 - 8.5	8.9 on 7.5	25.0	10.5	831	1356@44	400	A	A
235/45R17	94H	RRBL	17299	7.5 - 9.0	9.3 on 8.0	25.4	10.5	820	1477@44	400	A	A

1. The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

**WARNING:** Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owners manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires, and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owners manual for its recommendations.

**DANGER:** Never mount a 16" diameter tire on a 16.5" rim.  
**DANGER:** Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160 km/h (100 mph), load and inflation must be adjusted according to the table below.

**H-Speed Rated Sizes:**

Maximum Speed (mph)	100	106	112	118	124	130
Inflation Increase (psi)	0	1	2	3	4	5
Load Capacity (% of max.)	100	100	100	100	100	100

**V-Speed Rated Sizes:**

Maximum Speed (mph)	100	106	112	118	124	130	136	143	149
Inflation Increase (psi)	0	1	2	3	4	5	5	5	5
Load Capacity (% of max)	100	100	100	100	100	100	97	94	91