





The Michelin® Pilot® Primacy™ tire is a European-manufactured luxury performance touring tire designed to provide a superbly comfortable, quiet ride. In addition to its comfort capabilities, Pilot Primacy is also designed to offer a number of high performance characteristics, such as tight responsiveness and exceptional wet traction.



European Performance Profile



Dual Tread Design

Feel Every Curve

A European performance profile, featuring a rounder shoulder, is designed to provide progressive, predictable cornering, letting you push your vehicle to the edges of its performance capabilities.

Enjoy A Quiet, Comfortable Ride

Michelin® Comfort Control Technology™ helps deliver one of the most comfortable rides in the industry by using computer-optimized design and precision manufacturing to offer greatly reduced vibrations and road noise.

Remain Confident, Whether Rain Or Shine

A dual-asymmetric tread pattern, half-tuned for wet conditions and half-tuned for dry, promotes high performance levels, rain or shine.

Size	Service Desc.	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max. Load Single (lbs@psi)	Treadwear	Traction	Temperature	vw
205/55R16	91V MO	RRBL	18141	5.5 - 7.5	8.5 on 6.5	24.9	10.0	841	1356@51	240	AA	A	MB
225/50R16	92V MO	RRBL	20996	6.0 - 8.0	9.1 on 7.0	24.9	10.0	835	1389@51	240	AA	A	MB
225/50R16	92W MO	RRBL	23701	6.0 - 8.0	9.1 on 7.0	24.9	10.0	835	1389@51	240	AA	A	MB
225/55R16	95Y	RRBL	96285	6.0 - 8.0	9.2 on 7.0	25.8	10.0	812	1521@51	240	AA	A	AU
225/45R17	91W MO	RRBL	00649	7.0 - 8.5	9.0 on 7.5	24.9	10.0	841	1356@51	240	AA	A	MB
245/40R17	91W MO	RRBL	37547	8.0 - 9.5	9.8 on 8.5	24.7	10.0	841	1356@51	240	AA	A	MB
245/45R17	95W MO	RRBL	93929	7.5 - 9.0	9.6 on 8.0	25.7	10.0	810	1521@51	240	AA	A	MB
255/45R18	99V MO	RRBL	95188	8.0 - 9.5	10.0 on 8.5	27.0	10.0	777	1709@51	240	AA	A	MB
275/45R18	103V MO	RRBL	02403	8.5 - 10.5	10.7 on 9.0	27.8	10.0	748	1929@51	240	AA	A	MB
275/40ZR19/XL	105Y	RRBL	35151	9.0 - 11.0	11.0 on 9.5	27.6	10.0	755	2039@51	240	AA	A	VW

Service Description Key: MO = Mercedes-Benz
 Original Equipment Key: AU = Audi, MB = Mercedes-Benz, VW = Volkswagen.
 XL = Extra Load

- The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
- Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owners manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires, and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owners manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.
DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160 km/h (100 mph), load and inflation must be adjusted according to the table below.

V-Speed Rated Sizes:

Maximum Speed (mph)	100	106	112	118	124	130	136	143	149
Inflation Increase (psi)	0	1	2	3	4	5	5	5	5
Load Capacity (% of max)	100	100	100	100	100	100	97	94	91

W-Speed Rated Sizes:

Maximum Speed (mph)	118	124	130	136	143	149	155	161	168
Inflation Increase (psi)	0	1.5	3	4.5	6	7.5	7.5	7.5	7.5
Load Capacity (% of max)	100	100	100	100	100	100	95	90	85

Y-Speed Rated Sizes:

Maximum Speed (mph)	118	124	130	136	143	149	155	161	168	174	180	186
Inflation Increase (psi)	0	0	0	0	1.5	3	4.5	6	7.5	7.5	7.5	7.5
Load Capacity (% of max)	100	100	100	100	100	100	100	100	100	95	90	85

