



Size	Service Desc.	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max. Load Single (lbs@psi)	Treadwear	Traction	Temperature	Original Equipment
P205/65R15	92T	BW	43086	5.5 - 7.5	8.1 on 6.0	25.6	10.0	813	1400@44	600	A	B	
P205/70R15	95S	WW	51587	5.0 - 7.0	8.3 on 6.0	25.8	10.0	806	1499@44	600	A	B	
P215/70R15	97S	WW	78607	5.5 - 7.0	8.8 on 6.5	26.7	10.0	779	1620@44	600	A	B	
P215/65R16	96T	BW	67990	6.0 - 7.5	8.7 on 6.5	26.8	10.0	783	1565@44	600	A	B	HO
P225/60R16	97S	BW	43798	6.0 - 8.0	9.2 on 6.5	26.5	10.0	780	1609@35	600	A	B	F
P225/60R16	97S	BW	32333	6.0 - 8.0	9.2 on 6.5	26.8	10.0	777	1609@35	460	A	B	GM
P225/60R16	97S	WW6	98499	6.0 - 8.0	9.2 on 6.5	26.5	10.0	780	1609@35	600	A	B	F
225/60R16	98T	BW	85237	6.0 - 8.0	8.9 on 6.5	26.5	10.0	785	1653@44	600	A	A	HO
225/70R16/XL	107T	WW10	70891	6.0 - 7.5	9.0 on 6.5	28.4	10.0	732	2149@50	600	A	B	F
P235/60R16	99T	BW	82808	6.5 - 8.5	9.6 on 7.0	27.2	10.0	765	1709@44	600	A	B	F

Original Equipment Key: F = Ford, HO = Honda, GM = General Motors  
 XL = Extra Load

- The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.
- Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

**WARNING:** Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owners manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires, and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owners manual for its recommendations.

**DANGER:** Never mount a 16" diameter tire on a 16.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160 km/h (100 mph), load and inflation must be adjusted according to the table below.

**S-Speed Rated Sizes:**

Maximum Speed (mph)	100	106	112
Inflation Increase (psi)	0	1	2
Load Capacity (% of max.)	100	100	100

**T-Speed Rated Sizes:**

Maximum Speed (mph)	100	106	112	118
Inflation Increase (psi)	0	1	2	3
Load Capacity (% of max.)	100	100	100	100