

# TOYO TIRES™

## OPEN COUNTRY® H/T

The Open Country H/T is Toyo's new, all-season, highway type tire designed for optimal ride comfort, quiet performance and handling for urban and highway use. A wide range of direct Original Equipment replacement sizes are available for SUV's, Light Trucks and Crossover vehicles.

### Typical Vehicle Matches

Direct Original Equipment replacement for light trucks, SUV's and Crossover vehicles



### UTQG

P-Metric/Metric  
S- and T- rated sizes  
640 A B,  
H- and V rated sizes  
640 A A

### WARRANTY

P-Metric/Metric sizes:  
60,000 mile treadwear  
limited warranty.  
  
Light-Truck sizes:  
workmanship and  
materials only.

LIGHT TRUCK/SUV

Customer Benefit	Product Features
Quiet Ride	<ul style="list-style-type: none"> <li>• T-Mode Design Technology</li> <li>• Variable pitched tread blocks reduce noise generated between road and tire</li> <li>• Multi-wave sipes minimize heel and toe wear and worn tire noise</li> </ul>
Ride Comfort	<ul style="list-style-type: none"> <li>• T-Mode Design Technology</li> <li>• Optimized casing design ensures a smooth ride</li> <li>• Spiral-wound edge and cap ply (construction may vary by size)</li> <li>• Jointless bead wire</li> </ul>
Handling	<ul style="list-style-type: none"> <li>• High bead filler</li> <li>• Two wide steel belts</li> <li>• High turn-up polyester casing</li> <li>• Stability rib in shoulder area</li> </ul>
Durability and Treadlife	<ul style="list-style-type: none"> <li>• Cap/base construction</li> <li>• UTQG: S- and T- rated sizes 640 A B, H- rated 640 A A</li> <li>• Stability rib in shoulder area</li> <li>• Wide steel belt configuration</li> <li>• High turn-up polyester casing</li> </ul>
Wet Performance	<ul style="list-style-type: none"> <li>• Full-depth sipes continue to function as tire wears</li> <li>• Two deep evacuation grooves improve water channeling</li> </ul>
Styling	<ul style="list-style-type: none"> <li>• Embossed black letter and outline white letter sidewall styling</li> <li>• Rim protector</li> </ul>



**500 MILE  
of 45 DAY  
TRIAL OFFER  
AVAILABLE**  
LIMITED WARRANTY  
SEE FUR DETAILS

## OPEN COUNTRY® H/T

### UTQG

P-Metric/Metric  
S- and T- rated sizes  
640 A B,  
H- and V rated sizes  
640 A A

### WARRANTY

P-Metric/Metric sizes:  
60,000 mile treadwear  
limited warranty.

Light-Truck sizes:  
workmanship and  
materials only.

Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (%")	Inflated Dimensions		Static Loaded Radius (inch)	Max. Load (lbs.)		Max. Pressure (PSI)		Revs Per Mile	Price
					O.A.D. (inch)	O.A.W. (inch)		Single	Dual	Single	Dual		
<b>P-Metric/Metric</b>													
P225/75R15 102S*	362140	6.0-7.5	28	13	28.3	8.9	12.7	1874		35		733	
P235/75R15 105S*	362150	6.0-6.5-8.0	31	13	28.9	9.3	12.9	2028		35		719	
205/70R15 96H	362380	5.0-6.0-7.0	24	12	26.3	8.2	11.9	1565		44		789	
P225/70R15 100T*	362030	6.0-6.5-7.5	26	13	27.4	8.9	12.4	1753		35		757	
P235/70R15 102S*	362040	6.0-7.0-8.0	28	13	28.0	9.4	12.6	1896		35		743	
P265/70R15 110S	362050	7.0-8.0-9.0	37	13	29.6	10.4	13.2	2337		35		702	
P225/75R16 104S*	362160	6.0-7.5	31	13	29.3	8.9	13.2	1984		35		708	
P235/75R16 106S*	362660	6.0-6.5-8.0	34	13	29.8	9.4	13.4	2094		35		697	
P245/75R16 109S*	362170	6.5-7.0-8.0	40	13	30.4	9.8	13.6	2271		35		683	
P265/75R16 114T*	362180	7.0-7.5-9.0	41	13	31.5	10.4	14.1	2601		35		659	
P215/70R16 99H	362060	5.5-6.5-7.0	28	12	27.9	8.7	12.6	1709		35		744	
P225/70R16 101T*	362070	6.0-6.5-7.5	29	13	28.4	9.0	12.8	1819		35		731	
P235/70R16 104T*	362080	6.0-7.0-8.0	30	13	28.9	9.3	13.0	1984		35		718	
P245/70R16 106S*	362090	6.5-7.0-8.0	35	13	29.4	9.6	13.2	2094		35		706	
P255/70R16 109S*	362100	6.5-7.5-8.5	37	13	30.0	10.1	13.5	2271		35		692	
P265/70R16 111S*	362110	7.0-8.0-9.0	40	13	30.6	10.4	13.7	2403		35		678	
P275/70R16 114H	362120	7.0-8.0-9.0	41	13	31.1	10.8	13.9	2601		35		667	
215/65R16 98H	362340	6.0-6.5-7.5	25	12	27.0	8.8	12.3	1653		44		770	
P235/65R16 101S	362360	6.5-7.0-8.5	31	12	28.0	9.6	12.7	1819		35		741	
255/65R16 109H	362350	7.0-7.5-9.0	34	13	29.1	10.2	13.1	2271		44		715	
215/60R16 95H	362420	6.0-6.5-7.5	25	12	26.2	8.6	12.0	1521		44		794	
235/60R16 100H	362330	6.5-7.0-8.5	28	12	27.1	9.4	12.3	1764		44		767	
P235/75R17 108S*	362670	6.0-6.5-8.0	36	13	30.9	9.5	13.9	2205		35		673	
P245/75R17 110S*	362680	6.5-7.0-8.0	37	13	31.5	9.8	14.2	2337		35		660	
P235/70R17 108S RD*	362650	6.0-7.0-8.0	32	13	29.9	9.4	13.5	2205		41		695	
P245/70R17 108S*	362300	6.5-7.0-8.0	38	13	30.6	9.8	13.8	2205		35		680	
P255/70R17 110S*	362310	6.5-7.5-8.5	41	13	31.1	10.3	14.0	2337		35		668	
P265/70R17 113T*	362130	7.0-8.0-9.0	42	13	31.5	10.7	14.2	2535		35		659	
225/65R17 102H	362510	6.0-6.5-8.0	30	12	28.5	8.9	13.0	1874		44		729	
235/65R17 104H*	362370	6.5-7.0-8.5	33	12	29.0	9.4	13.2	1984		44		716	
P245/65R17 105H*	362010	7.0-8.5	34	13	29.5	9.7	13.4	2039		35		704	
P255/65R17 108S	362430	7.0-7.5-9.0	38	13	30.1	10.3	13.6	2205		35		681	
P265/65R17 110S*	362020	7.5-8.0-9.5	40	13	30.5	10.6	13.8	2337		35		682	
275/65R17 115T	362390	7.5-8.0-9.5	40	13	31.1	11.0	14.0	2679		44		668	
P235/60R17 100S	362630	6.5-7.0-8.5	32	11	28.2	9.4	12.9	1764		35		737	
255/60R17 106H	362590	7.0-7.5-9.0	35	13	29.1	10.3	13.2	2094		44		715	
255/70R18 113S	362610	6.5-7.5-8.5	39	12	32.2	10.4	14.5	2535		44		646	
P265/70R18 114S*	362320	7.0-8.0-9.0	44	13	32.6	10.8	14.7	2601		35		636	
P235/65R18 104T	362640	6.5-7.0-8.5	32	12	30.2	9.6	13.7	1984		35		689	
P275/65R18 114T*	362470	7.0-8.0-9.5	45	13	32.2	11.0	14.5	2601		35		646	

\*Indicates white letter styling. RD = Reinforced

Bold designates measuring rim width.

All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.

**LIGHT TRUCK/SUV**

# TOYO TIRES™



**500 MILE  
or 45 DAY  
TRIAL OFFER  
AVAILABLE**  
LIMITED WARRANTY  
SEE FOR DETAILS

## OPEN COUNTRY® H/T

### UTQG

P-Metric/Metric  
S- and T- rated sizes  
640 A B,  
H- and V rated sizes  
640 A A

### WARRANTY

P-Metric/Metric sizes:  
60,000 mile treadwear  
limited warranty.

Light-Truck sizes:  
workmanship and  
materials only.

Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (%")	Inflated Dimensions		Static Loaded Radius (inch)	Max. Load (lbs.)		Max. Pressure (PSI)		Revs Per Mile	Price
					O.A.D. (inch)	O.A.W. (inch)		Single	Dual	Single	Dual		
<b>P-Metric/Metric (continued)</b>													
235/60R18 107V RD	362560	6.5-7.0-8.5	33	11	29.1	9.4	13.3	2150		50		714	
255/60R18 112H RD	362600	7.0-7.5-9.0	37	13	30.0	10.1	13.7	2469		50		692	
P265/60R18 109T	362460	7.0-8.0-9.5	37	13	30.5	10.6	13.9	2271		35		682	
P275/60R18 111H	362710	7.5-8.0-9.5	39	13	30.8	10.9	14.0	2403		35		675	
235/55R18 100V†	362400	6.5-7.5-8.5	27	10	28.1	9.6	13.0	1764		44		738	
255/55R18 109V RD	362570	7.0-8.0-9.0	36	12	29.1	10.4	13.3	2271		50		715	
255/55R19 111V RD	362580	7.0-8.0-9.0	37	12	30.0	10.4	13.8	2403		50		692	
265/50R20 112V RD	362690	7.5-8.5-9.5	40	11	30.4	10.9	14.1	2403		50		683	
275/55R20 117S RD*	362700	7.5-8.5-9.5	42	13	31.9	11.4	14.6	2833		50		651	
285/45R22 114H RD	362720	9.0-9.5-10.5	43	12	32.0	11.2	14.9	2601		50		648	
<b>Light Truck</b>													
LT235/75R15 104/101S C/6*	362210	6.0-6.5-7.0	34	14	28.8	9.5	12.9	1985	1820	50	50	722	
31x10.50R15 109S C/6*	362000	7.0-8.5-9.0	43	16	30.3	10.9	13.5	2270		50		685	
LT215/85R16 115/112S E/10	362290	5.5-6.0-7.0	41	15	30.4	8.9	13.6	2680	2470	80	80	683	
LT235/85R16 120/116S E/10*	362280	6.0-6.5-7.5	44	15	31.8	9.4	14.2	3042	2778	80	80	654	
LT225/75R16 115/112S E/10	362220	<b>6.0-7.0</b>	39	14	29.3	9.1	13.2	2680	2470	80	80	710	
LT245/75R16 120/116S E/10*	362230	<b>6.5-8.0</b>	45	15	30.4	9.8	13.6	3042	2778	80	80	684	
LT265/75R16 112/109S C/6*	362240	7.0-7.5-8.0	45	16	31.6	10.8	14.1	2470	2270	50	50	658	
LT265/75R16 119/116S D/8*	362250	7.0-7.5-8.0	49	16	31.6	10.8	14.1	3000	2755	65	65	658	
LT265/75R16 123/120S E/10*	362260	7.0-7.5-8.0	50	16	31.6	10.8	14.1	3415	3085	80	80	658	
LT235/80R17 120/117S E/10	362270	6.0-6.5-7.5	43	15	31.7	9.2	14.2	3085	2835	80	80	655	
LT245/75R17 121S E/10*	362620	6.5-7.0-7.5	47	15	31.5	9.9	14.2	3195		80		660	
LT245/70R17 119/116S E/10*	362190	6.5-7.0-8.0	44	15	30.5	9.8	13.8	3000	2755	80	80	681	
LT265/70R17 121/118S E/10*	362200	7.0-8.0-8.5	50	16	31.6	10.7	14.2	3195	2910	80	80	658	
LT275/70R18 125S E/10	362450	7.0-8.0-8.5	52	16	33.1	11.0	14.9	3640		80		628	
LT275/65R18 123S E/10	362480	7.5-8.0-9.0	52	16	32.0	10.9	14.4	3415		80		650	

\*Indicates white letter styling. RD = Reinforced †UTQG 600 A A.

Bold designates measuring rim width.

All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.



LIGHT TRUCK/SUV