

# TOYO TIRES™

PERFORMANCE

## **PROXES® S/T** **HIGH-PERFORMANCE CROSSOVER, SPORT TRUCK** **AND SUV RADIAL**

*The Proxes S/T is a high-performance tire that delivers a powerful combination of superb handling, confident all-season performance and a smooth, stable ride. The H, V, W and Y speed-rated Proxes S/T offers plus-sizing opportunities on pickup trucks, sport utility vehicles and Original Equipment fitments on high-performance crossover SUVs.*

### **Typical Vehicle Matches**

Chevrolet Tahoe, Suburban, C/K pickups; Dodge Durango, Ram; Ford Expedition, F-150 pickups; GMC Yukon, Jimmy, Sierra; Infiniti QX4; Jeep Grand Cherokee; Lexus LX 470; Mercedes-Benz ML320, ML430; Nissan Pathfinder. OE fitments for: VW Toureg; Nissan Murano, FX45; BMW X5; Land Rover.



**UTQG**  
420 A A  
Y-Rated sizes  
280 A A

<b>Customer Benefit</b>	<b>Product Features</b>
Wet and Dry Handling	<ul style="list-style-type: none"> <li>• Computer-optimized, unidirectional, all-season tread design</li> <li>• Angled tread grooves</li> <li>• Cap/base tread compound</li> <li>• H, V, W and Y speed-rated</li> </ul>
Steering Response	<ul style="list-style-type: none"> <li>• Specially engineered polyester casing</li> <li>• High-ply turn-up construction</li> <li>• High bead filler</li> <li>• Two wide, high-tensile steel belts</li> </ul>
All-Season Performance	<ul style="list-style-type: none"> <li>• Computer-optimized, unidirectional all-season tread design</li> <li>• Double V-shaped tread grooves</li> <li>• Cap/base tread compound</li> <li>• M&amp;S rated</li> </ul>
Quiet, Stable Ride	<ul style="list-style-type: none"> <li>• Computer-optimized, unidirectional all-season tread design</li> <li>• Jointless bead wire</li> <li>• Jointless cap ply (construction may vary by size)</li> <li>• Two wide, high-tensile steel belts</li> </ul>
Durability and Long Life	<ul style="list-style-type: none"> <li>• Jointless bead wire</li> <li>• Two wide, high-tensile steel belts</li> <li>• Cap/base tread compound</li> <li>• Rim protector</li> </ul>
Sporty Appearance	<ul style="list-style-type: none"> <li>• Wide, low-profile design</li> <li>• Ultra-modern sidewall styling</li> <li>• Aggressive, unidirectional all-season tread design</li> </ul>



## PROXES® S/T HIGH-PERFORMANCE CROSSOVER, SPORT TRUCK AND SUV RADIAL



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (32")	Inflated Dimension		Static Loaded Radius (inch)	Max. Load (lbs.)	Max. Pressure (PSI)	Revs Per Mile	Price
					Overall Diameter (inch)	Overall Width (inch)					
P275/60R15 107H	242100	7.5-8.0-9.5	30	11	28.0	11.0	12.5	2149	44	744	
P295/50R15 105H	242120	8.0-9.5-10.0	34	11	26.7	12.2	12.0	2061	44	783	
245/70R16 107V	242660	6.5-7.0-8.0	34	11	29.6	9.7	13.3	2149	44	702	
265/70R16 112V	242670	7.0-8.0-9.0	39	11	30.7	10.3	13.7	2469	44	676	
275/70R16 114H	242190	7.0-8.0-9.0	38	11	31.2	11.0	14.0	2601	44	664	
275/60R16 109V	242180	7.5-8.0-9.5	40	11	29.0	11.0	13.0	2271	44	720	
235/65R17 104V	242640	6.5-7.5-8.5	31	10	28.9	9.4	13.2	1984	44	718	
285/60R17 110V RD	242240	7.0-7.5-9.0	37	11	29.1	10.2	13.2	2337	50	717	
275/60R17 111V	242220	7.5-8.0-9.5	39	11	30.0	11.0	13.5	2403	44	694	
285/60R17 114V	242230	8.0-8.5-10.0	42	11	30.5	11.5	13.7	2601	44	683	
225/55R17 97V	242630	6.0-7.0-8.0	27	11	26.7	9.1	12.3	1609	44	777	
275/55R17 109V	242620	7.5-8.5-9.5	38	11	28.9	11.1	13.1	2271	44	720	
225/65R18 103V	242770	6.0-6.5-8.0	31	10	29.4	8.9	13.5	1929	44	705	
255/60R18 112V RD	242650	7.0-8.0-9.0	37	11	30.0	10.4	13.7	2469	50	693	
285/60R18 116 V	242270	8.0-8.5-10.0	43	11	31.5	11.5	14.3	2756	44	661	
305/60R18 120V	242290	8.5-9.0-11.0	47	12	32.4	12.0	12.6	3086	44	645	
255/55R18 109V RD	242160	7.0-8.0-9.0	34	11	29.0	10.4	13.3	2271	50	718	
275/55R18 114V RD	242480	7.5-8.5-9.5	39	11	29.8	11.1	13.6	2601	50	696	
255/50R18 106V RD	242470	7.0-8.0-9.0	34	11	27.9	10.2	12.9	2094	50	744	
285/50R18 109V	242610	8.0-9.0-10.0	37	11	29.1	10.4	13.3	2271	44	715	
255/45R18 99V	242590	8.0-8.5-9.5	30	10	27.1	10.0	12.5	1709	44	767	
295/45R18 108V	242280	9.5-10.0-11.0	39	11	28.5	11.7	13.0	2205	44	733	
255/55R19 111V RD	242780	7.0-8.0-9.0	35	11	30.0	10.4	13.8	2403	50	692	
255/50R19 103V	242600	7.0-8.0-9.0	36	11	29.1	10.4	13.4	1929	44	714	
275/45R19 108Y RD*	242580	8.5-9.0-10.5	34	10	28.8	10.7	13.3	2205	50	722	
285/45R19 107V	242570	9.0-9.5-10.5	35	11	29.1	11.2	13.4	2149	44	714	
275/55R20 117V RD	242800	7.5-8.5-9.5	41	11	31.9	11.0	14.6	2833	50	652	
255/50R20 109V RD	242490	7.0-8.0-9.0	31	11	29.9	10.2	13.9	2271	50	694	
265/50R20 111V RD	242330	7.5-8.5-9.5	39	11	30.4	11.0	14.1	2403	50	683	
285/50R20 116V RD	242710	8.0-9.0-10.0	42	11	31.1	11.6	14.3	2756	50	669	
305/50R20 120V RD	242350	8.5-9.5-11.0	45	11	32.1	12.4	14.6	3086	50	651	
325/50R20 120V	242340	9.0-10.0-11.5	49	12	32.8	13.2	12.7	3086	44	636	
255/45R20 105V RD	242450	8.0-8.5-9.5	33	11	29.1	10.1	13.5	2039	50	714	
265/45R20 108V RD	242560	8.5-9.0-10.0	34	10	29.4	10.5	13.7	2205	50	707	
275/45R20 110V RD	242790	8.5-9.0-10.5	34	11	29.8	10.6	13.8	2337	50	698	
295/45R20 114V RD	242320	9.5-10.0-11.0	40	11	30.5	11.7	14.1	2601	50	683	
255/40R20 101V RD	242700	8.5-9.0-10.0	30	10	28.0	10.1	13.1	1819	50	743	
275/40R20 106W RD	242740	9.0-9.5-11.0	34	11	28.6	10.8	13.3	2094	50	727	
295/40R20 106V	242510	10.0-10.5-11.5	36	10	29.2	11.7	13.6	2094	44	711	
315/35R20 106W	242540	10.5-11.0-12.5	35	11	28.6	12.3	13.3	2094	44	727	
325/50R22 120V	242680	9.0-10.0-11.5	61	11	34.7	13.0	15.9	3086	44	599	
285/45R22 114V RD	242690	9.0-9.5-10.5	42	11	32.2	11.2	15.0	2601	50	645	
305/45R22 118V RD	242370	9.5-10.0-11.5	48	11	32.8	12.0	15.2	2910	50	636	
265/40R22 106V RD	242460	9.0-9.5-10.5	45	11	30.4	10.7	14.3	2094	50	684	
305/40R22 114V RD	242390	10.0-10.5-12.0	45	11	31.6	12.3	14.7	2601	50	657	
325/40R22 118V RD	242360	11.0-11.5-13.0	49	11	32.2	12.8	15.0	2910	50	644	
265/35R22 102W RD	242760	9.0-9.5-10.5	34	10	29.3	10.4	13.9	1874	50	708	
285/35R22 106W RD	242750	9.5-10.0-11.0	37	11	29.8	11.3	14.0	2094	50	697	
295/30R22 103Y RD*	242520	10.0-10.5-11.0	36	10	29.1	11.5	13.8	1929	50	715	
315/30R22 107Y RD*	242830	10.5-11.0-11.5	37	11	29.5	12.2	13.9	2149	50	704	
305/40R23 115V RD	242380	10.0-11.0-12.0	45	11	32.6	12.0	15.3	2679	50	636	
285/35R23 107V RD	242500	9.5-10.0-11.0	40	11	30.9	11.3	14.6	2149	50	671	
325/45R24 120V	242730	10.0-11.0-12.0	54	11	35.4	12.6	16.4	3086	44	588	
285/40R24 112V RD	242720	9.5-10.0-11.0	46	11	32.9	11.3	15.5	2469	50	631	
305/35R24 112V RD	242820	10.0-11.0-12.0	42	11	32.5	12.1	15.3	2469	50	640	
295/30R24 105V RD	242810	10.0-10.5-11.0	39	11	31.1	11.4	14.8	2039	50	668	

\* UTQG rating is 280 A A, summer tires only, not M&S rated. RD = Reinforced. Rim protector on all sizes. Bold designates measuring rim width. When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph. All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information. See Toyo Safety Advisory for Lifted Light Trucks, Page 40