

Tire Catalog

Long Touring A/S

A long lasting tire that provides great value for passenger cars and minivans. Available only at Wal-Mart®.

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load (lbs@psi)
P195/65R15	89T	BSW	05883	5.5 - 7	6 on 6	25	11	832	1279@44
P205/65R15	92T	BSW	28137	5.5 - 7.5	6.3 on 6	25.5	11	816	1400@44
P215/70R15	97T	BSW	33195	5.5 - 7	6.6 on 6.5	26.9	11	773	1620@44
P205/55R16	89T	BSW	07536	5.5 - 7.5	6.9 on 6.5	24.9	11	835	1279@44
P215/60R16	94T	BSW	05302	6 - 7.5	6.6 on 6.5	26.1	11	797	1477@44
P225/60R16	97T	BSW	23683	6 - 8	7 on 6.5	26.6	11	782	1609@44

- The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height
- Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle o

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating t

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the

For speeds over 160km/h (100 mph), load and inflation must be adjusted according to the table below.

T-Speed Rated Sizes:

Maximum Speed (mph)	100	106	112	118	
Inflation Increase (psi)		0.0	1.0	2.0	3.0
Load Capacity (% of max.)		100	100	100	100

The **Uniform Tire Quality Grading Ratings (UTQG)** is a tire information system designed to help you make the relative comparisons among all passenger car tires. The UTQG rating tells you about the tire's treadwear, traction, and temperature grades.

Size	Treadwear	Traction	Temperature
P195/65R15	620	A	B
P205/65R15	620	A	B
P215/70R15	620	A	B
P205/55R16	620	A	B
P215/60R16	620	A	B
P225/60R16	620	A	B